

Diametro		Peso	Tolleranza Standard	Tolleranza		Tolleranza Standard	Tolleranza		Tolleranza Standard	Tolleranza
mm	inch.	kg/m		mm			mm			mm
8		0,394	h7	+ 0 / - 0,015		f7	- 0,013 / - 0,028		f8	- 0,013 / - 0,035
10		0,616								
12		0,887								
14		1,208	h7	+ 0 / - 0,018		f7	- 0,020 / - 0,041		f8	- 0,016 / - 0,043
15		1,387								
16		1,578								
17		1,781								
18		1,997								
19		2,225								
19,05	3/4"	2,236	h7	+ 0 / - 0,021		f7	- 0,020 / - 0,041		f8	- 0,020 / - 0,053
20		2,465								
22		2,983								
22,22	7/8"	3,042								
24		3,549								
25		3,851								
25,4	1"	3,976								
28		4,831								
28,57	1,1/8"	5,030								
30		5,546								
31,75	1,1/4"	6,212								
32		6,310								
35		7,549	h7	+ 0 / - 0,025		f7	- 0,025 / - 0,050		f8	- 0,025 / - 0,064
36		7,986								
38		8,898								
38,1	1,1/2"	8,945								
40		9,860								
42		10,870								
44,45	1,3/4"	12,175								
45		12,479								
50		15,406								
50,8	2"	15,903								
55		18,641	h7	+ 0 / - 0,030		f7	- 0,030 / - 0,060		f8	- 0,030 / - 0,066
56		19,325								
57,15	2,1/4"	20,127								
60		22,184								
63		24,458								
63,5	2,1/2"	24,848								
65		26,036								
70		30,195								
72		31,945								
75		34,663								
76,2	3"	35,781								
80		39,438								
82,55	3,1/4"	41,993								
85		44,522								
88,9	3,1/2"	48,702								
90		49,914	h7	+ 0 / - 0,035		f7	- 0,036 / - 0,071		f8	- 0,036 / - 0,090
95		55,614								
100		61,623								
101,6	4"	63,610								
105		67,939								
110		74,563								
114,3	4,1/2"	80,507								
115		81,496								
120		88,736								
125		96,285								
127	5"	99,391	h7	+ 0 / - 0,040		f7	- 0,043 / - 0,083		f8	- 0,043 / - 0,106
130		104,142								
140		120,780								