

Diametro		Peso	Tolleranza Standard	Tolleranza mm	Tolleranza Standard	Tolleranza mm	Tolleranza Standard	Tolleranza mm
mm	inch.	kg/m						
8		0,394	h7	+ 0 / - 0,015	f7	- 0,013 / - 0,028	f8	- 0,013 / - 0,035
10		0,616						
12		0,887						
14		1,208	h7	+ 0 / - 0,018	f7	- 0,020 / - 0,041	f8	- 0,013 / - 0,043
15		1,387						
16		1,578						
17		1,781						
18		1,997						
19		2,225						
19,05	3/4"	2,236	h7	+ 0 / - 0,021	f7	- 0,020 / - 0,041	f8	- 0,020 / - 0,053
20		2,465						
22		2,983						
22,22	7/8"	3,042						
24		3,549						
25		3,851						
25,4	1"	3,976						
28		4,831						
28,57	1,1/8"	5,030						
30		5,546						
31,75	1,1/4"	6,212						
32		6,310						
35		7,549						
36		7,986						
38		8,898						
38,1	1,1/2"	8,945						
40		9,860						
42		10,870						
44,45	1,3/4"	12,175						
45		12,479						
50		15,406	h7	+ 0 / - 0,030	f7	- 0,030 / - 0,060	f8	- 0,030 / - 0,066
50,8	2"	15,903						
55		18,641						
56		19,325						
57,15	2,1/4"	20,127						
60		22,184						
63		24,458						
63,5	2,1/2"	24,848						
65		26,036						
70		30,195						
72		31,945						
75		34,663	h7	+ 0 / - 0,035	f7	- 0,036 / - 0,071	f8	- 0,036 / - 0,090
76,2	3"	35,781						
80		39,438						
82,55	3,1/4"	41,993						
85		44,522						
88,9	3,1/2"	48,702						
90		49,914						
95		55,614						
100		61,623						
101,6	4"	63,610						
105		67,939						
110		74,563	h7	+ 0 / - 0,040	f7	- 0,043 / - 0,083	f8	- 0,043 / - 0,106
114,3	4,1/2"	80,507						
115		81,496						
120		88,736						
125		96,285						
127	5"	99,391						
130		104,142						
140		120,780						